

FORM PTO-1590 (Modified) (REV 11-98)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER 112740-221
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371			U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 09/856841)
INTERNATIONAL APPLICATION NO. PCT/DE99/03633	INTERNATIONAL FILING DATE 15 November 1999	PRIORITY DATE CLAIMED 25 November 1998	
TITLE OF INVENTION IDSN NETWORK WITH A HARDWARE PLATFORM IN SWITCHING CENTERS			
APPLICANT(S) FOR DO/EO/US Christian Maierhofer			
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:			
<ol style="list-style-type: none"> 1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. 3. <input checked="" type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1). 4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date. 5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371 (c) (2)) <ol style="list-style-type: none"> a. <input checked="" type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> has been transmitted by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 6. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)). 7. <input checked="" type="checkbox"/> A copy of the International Search Report (PCT/ISA/210). 8. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3)) <ol style="list-style-type: none"> a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). b. <input checked="" type="checkbox"/> have been transmitted by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input type="checkbox"/> have not been made and will not be made. 9. <input checked="" type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 10. <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)). 11. <input checked="" type="checkbox"/> A copy of the International Preliminary Examination Report (PCT/IPEA/409). 12. <input type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)). 			
Items 13 to 20 below concern document(s) or information included:			
<ol style="list-style-type: none"> 13. <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 14. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 15. <input checked="" type="checkbox"/> A FIRST preliminary amendment. 16. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. 17. <input checked="" type="checkbox"/> A substitute specification. 18. <input type="checkbox"/> A change of power of attorney and/or address letter. 19. <input checked="" type="checkbox"/> Certificate of Mailing by Express Mail 20. <input checked="" type="checkbox"/> Other items or information: 			
Submission of Drawings - Figures 1-2 on two sheets			

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 1.53) 09/856841		INTERNATIONAL APPLICATION NO. PCT/DE99/03633		ATTORNEY'S DOCKET NUMBER 112740-221	
---	--	--	--	---	--

21. The following fees are submitted: BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) : <input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$1,000.00 <input checked="" type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$860.00 <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$710.00 <input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$690.00 <input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00 <p style="text-align: center;">ENTER APPROPRIATE BASIC FEE AMOUNT =</p>				CALCULATIONS PTO USE ONLY <div style="border: 1px solid black; height: 100px; width: 100%;"></div>	
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).				\$0.00	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	4 - 20 =	0	x \$18.00	\$0.00	
Independent claims	1 - 3 =	0	x \$80.00	\$0.00	
Multiple Dependent Claims (check if applicable). <input type="checkbox"/>				\$0.00	
TOTAL OF ABOVE CALCULATIONS =				\$860.00	
Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable). <input type="checkbox"/>				\$0.00	
SUBTOTAL =				\$860.00	
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).				\$0.00	
TOTAL NATIONAL FEE =				\$860.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). <input type="checkbox"/>				\$0.00	
TOTAL FEES ENCLOSED =				\$860.00	
				Amount to be:	\$
				refunded	
				charged	\$

☒ A check in the amount of **\$860.00** to cover the above fees is enclosed.

☐ Please charge my Deposit Account No. _____ in the amount of _____ to cover the above fees.
 A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. **02-1818** A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

William E. Vaughan (Reg. No. 39,056)
Bell, Boyd & Lloyd LLC
P.O. Box 1135
Chicago, Illinois 60690

William E. Vaughan
 NAME

39, 056
 REGISTRATION NUMBER

May 25, 2001
 DATE

BOX PCT

IN THE UNITED STATES ELECTED/DESIGNATED OFFICE
OF THE UNITED STATES PATENT AND TRADEMARK OFFICE
UNDER THE PATENT COOPERATION TREATY-CHAPTER II

5

PRELIMINARY AMENDMENT

APPLICANT: Christian Maierhofer DOCKET NO: 112740-221
SERIAL NO: GROUP ART UNIT:
EXAMINER:
INTERNATIONAL APPLICATION NO: PCT/DE99/03633
INTERNATIONAL FILING DATE: 15 November 1999
INVENTION: ISDN NETWORK WITH A HARDWARE PLATFORM IN
SWITCHING CENTERS

10

15

Assistant Commissioner for Patents,
Washington, D.C. 20231

20

Sir:
Please amend the above-identified International Application before entry into
the National stage before the U.S. Patent and Trademark Office under 35 U.S.C. §371
as follows:

In the Specification:

25

Please replace the Specification of the present application, including the
Abstract, with the following Substitute Specification:

S P E C I F I C A T I O N**TITLE**

**ISDN NETWORK WITH A HARDWARE PLATFORM IN SWITCHING
CENTERS**

BACKGROUND OF THE INVENTION**Field of the Invention**

The present invention relates to an ISDN network with switching centers to
which data-compatible terminals, e.g. in the form of computers with ISDN cards, are

also connected, wherein the switching centers include a switching network and a coordination processor with user programs, and the network is configured to allow an exchange of data between the data-compatible terminals and the coordination processor as defined by the user programs.

5 **Description of the Prior Art**

Operator systems providing information and/or switching services are typical examples of data exchange between a data-compatible terminal and a digital switching center, where network-wide data connections are to be established between the terminals of operator-console systems and the digital controller of a digital exchange.

10 According to known proposals, a data connection is established over the ISDN D channel in order to transfer internal data, though network-wide transfer via the network is not possible between port-based user programs. However, the small data volume that can be transferred per time unit, which is theoretically 16 kbit/s for an ISDN D channel (though this transfer rate is only partially achieved), has an adverse
15 effect in practice, since the D channel is also used for ISDN signaling. As a result, it cannot be used for relatively large data volumes, such as, for example, in the case of software updates requiring several Mbytes.

WO 98/17079 (Siemens Aktiengesellschaft) describes a method for handling service connections in a digital network, which enables a subscriber with a digital
20 terminal to access the Internet via the fastest possible path. A suitable switching center contains what is known as a "POP" server, to which a line trunk group is assigned, and where the POP server is a hardware platform.

However, the present application concerns a switching center that includes a coordination processor with user programs that relate to operator consoles, for
25 example, where large data volumes may occur.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a way by which relatively large data volumes can be transferred over data connections between data-compatible terminals and the software of the coordination processor in a switching center, with

facilities for sending large data volumes automatically; e.g., at times of low network utilization.

Based on an ISDN network of the type described at the beginning, the present invention achieves this by installing a hardware platform in at least one switching center, the hardware platform being assigned a unique call number throughout the network, and a direct bus connection being provided between this hardware platform and the coordination processor. The platform implements the data traffic with the terminals via B channels and the coordination processor is configured in conjunction with a user program to dial up terminals directly via a subscriber call number.

Using the present invention, a data-compatible terminal can dial up the hardware platform directly, so that data from the user programs can be sent to the terminals via the direct bus connection. Since the data traffic now flows via B channels of the ISDN network, it is possible to transfer considerably greater data volumes, i.e. up to 64 kbit/s and, if necessary, the intelligent digital switching center can also establish a data connection with a data-compatible terminal.

For transferring relatively large data volumes, it is also expedient to configure the hardware platform to support data traffic with a terminal via both B channels.

For security reasons, it is also possible to assign the hardware platform a call number that cannot be dialed.

Additional features and advantages of the present invention are described in, and will be apparent from, the following Detailed Description of the Preferred Embodiments and the Drawings.

DESCRIPTION OF THE DRAWINGS

Figure 1 shows the schematic layout of a switching center with a connected terminal and a state-of-the-art operator console; and

Figure 2 schematically shows an ISDN network of the present invention with two switching centers, together with connected terminals or operator consoles.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

According to Figure 1, a local switching center LVS has a coordination processor COP, a switching network KNE, and an access unit ASE. A data-compatible

terminal EGE may consist of a PC with an ISDN card ISC, for example, and this PC has access to user programs UPR. Using an ISDN basic access IBA, data can be transferred with the switching center LVS over the ISDN D channel. As described in, for example "ISDN - Digitale Netze für Sprachen, Text, Daten, Video und Multimedia-Kommunikation" [ISDN - digital networks for voice, text, data, video and multimedia communication] by Peter Bocker, 4th edition, Springer Verlag 1997, ISBN 3-45-57431-X, each basic access gives a user two 64-kbit/s basic channels, known as B channels, and one 16-kbit/s auxiliary channel, known as the D channel, in each direction. The data stream from a number of ISDN basic accesses, up to approximately 500 in practice, is concentrated in the access units ASE onto a message channel with 64 kbit/s leading to the coordination processor COP, and the data are routed to the individual user programs UPR1, UPR2 and UPR3 from there. Such user programs may be implemented to manage or support a switching operation, for example, where an operator console OPP is provided, such as for manual switching. The switching center LVS shown in Figure 1 is a local switching center, and provides the only data connection available to the terminal EGE. No network-wide data connections are therefore possible, in addition to which the data transfer is restricted to 16 kbit/s per terminal. Furthermore, the combination of several ISDN basic accesses on one internal message channel of the switching center LVS creates an undesirable bottleneck.

By contrast, as shown in Figure 2, the present invention proposes a hardware platform HWP in a switching center LVSR, in addition to the coordination processor COP with the user programs UPR1, UPR2 and UPR3, and a switching network KNE which hardware platform HWP is connected directly to the ports of the line trunk group LTG on one side, and via a direct bus connection BUV to the coordination processor (COP) and its user programs UPR1, UPR2 and UPR3 on the other side. It should be noted that, in principle, a switching center LVSR can be implemented as what is known as an EWSD (Siemens digital electronic switching system), as described in, for example, "Telekommunikationstechnik" [Telecommunications systems] by Ottfried Georg, in Chapter 7.3 of "Das Vermittlungssystem EWSD" [the EWSD switching system], Springer Verlag 1996, ISBN 3-45-61381-1.

As is evident, the actual ISDN network NET also includes other switching centers, such as the switching center LVSr shown on the left of the diagram with a switching network KNE and other equipment not shown here, to which a further terminal EGEr is, in turn, connected via an ISDN basic access IBA, and where this
5 terminal likewise includes an ISDN card ISC and user programs UPR.

During operation, the ISDN card ISC of a terminal EGE, for example, initiates an outgoing call over the B channel to the hardware platform, where it is expedient to use a "non-dialable" number for this purpose, e.g., "0F10". "Non-dialable" refers to the number not being able to be dialed using a conventional keypad, which only has
10 numbers, and is expedient for security reasons. The remote switching center, namely the switching center LVSr on the left of the diagram in this case, analyzes the dialed number and routes the call through the public exchange to the destination switching center LVSR where the digits in the call number are analyzed, and traffic for the internal hardware platform HWP is identified. The next step is to find a free port for
15 access to the hardware platform HWP, this being performed by the routing functions of the switching center LVSR.

As mentioned previously, the ports assigned to the hardware platform HWP are connected within the switching center to the line trunk group LTG for outgoing lines or subscribers. The hardware platform HWP now handles the data transfer protocol
20 with the terminals, and the hardware platform HWP transfers data to the user programs UPR1, UPR2 and UPR3 in the coordination processor COP. Furthermore, the hardware platform HWP accepts data from the user programs and sends them to the terminals EGEr. In this context, the hardware platform HWP is directly connected to the central controller, namely the coordination processor COP, via the bus connection
25 BUUV, and uses interprocessor messages to communicate with the user programs. The user programs UPR1, UPR2 and UPR3 in the coordination processor COP receive the data from the hardware platform HWP. If a user program wants to send data back to the terminal EGEr, it uses an interprocessor message to transfer them to the hardware platform, which can dial up terminals directly via a subscriber call number. It is also

expedient for the hardware platform HWP to be configured to support data traffic with a terminal via both B channels, in order to allow higher data throughput.

Although the present invention has been described with reference to specific embodiments, those of skill in the art will recognize that changes may be made thereto without departing from the spirit and scope of the invention as set forth in the hereafter appended claims.

ABSTRACT OF THE DISCLOSURE

An ISDN network with switching centers, to which data-compatible terminals, e.g. in the form of computers with ISDN cards, are also connected, wherein the switching centers include a switching network and a coordination processor with user programs, and wherein the network is configured to allow an exchange of data between the data-compatible terminals and the coordination processor as defined by the user programs, and wherein, a hardware platform is installed in at least one switching center and is assigned a unique call number throughout the network, and a direct bus connection is provided between this hardware platform and the coordination processor, where the platform implements the data traffic with the terminals via B channels.

In the claims:

On page 6, cancel line 1, and substitute the following left-hand justified heading therefor:

I Claim as My Invention:

Please cancel claims 1-4, without prejudice, and substitute the following claims therefor:

6. An ISDN network, comprising:

a public exchange;

a plurality of switching centers connected via the public exchange, each of the plurality of switching centers including a switching network and a coordination processor with user programs;

a plurality of data-compatible terminals formed of computers with ISDN cards, each of the plurality of data-compatible terminals being connected to one of the plurality of switching centers, such that data exchange is allowed between the plurality

of data-compatible terminals and the coordination processors as defined by the user programs;

a hardware platform installed in at least one of the plurality of switching centers, the hardware platform being assigned a unique call number throughout the
5 ISDN network; and

a direct bus connection provided between the hardware platform and the associated coordination processor;

wherein the hardware platform implements the data exchange traffic with the plurality of data-compatible terminals via B channels, and the coordination processors
10 are configured in conjunction with the user programs to dial up the plurality of data-compatible terminals directly via a subscriber call number.

7. An ISDN network as claimed in claim 6, wherein the hardware platform is configured to support the data traffic with one of the plurality of data-
15 compatible terminals via two B channels.

8. An ISDN network as claimed in claim 6, wherein the unique call number assigned to the hardware platform is a non-diallable call number.

9. An ISDN network as claimed in claim 6, wherein the hardware platform is directly connected to ports of a line trunk group.

REMARKS

The present amendment makes editorial changes and corrects typographical errors in the specification, which includes the Abstract, in order to conform the
25 specification to the requirements of United States Patent Practice. No new matter is added thereby. Attached hereto is a marked-up version of the changes made to the specification by the present amendment. The attached page is captioned "**Version With Markings To Show Changes Made**".


In addition, the present amendment cancels original claims 1-4 in favor of
30 new claims 6-9. Claims 6-9 have been presented solely because the revisions by

red-lining and underlining which would have been necessary in claims 1-4 in order to present those claims in accordance with preferred United States Patent Practice would have been too extensive, and thus would have been too burdensome. The present amendment is intended for clarification purposes only and not for

5 substantial reasons related to patentability pursuant to 35 USC §§103, 102, 103 or 112. Indeed, the cancellation of claims 1-4 does not constitute an intent on the part of the Applicant to surrender any of the subject matter of claims 1-4.

Early consideration on the merits is respectfully requested.

Respectfully submitted,



William E. Vaughan
Bell, Boyd & Lloyd LLC
P.O. Box 1135
Chicago, Illinois 60690-1135
(312) 807-4292
Attorneys for Applicants

(Reg. No. 39,056)

10-30-2000

199805815

- 1 -

DE 009903633

Description

Method for handling service connections in a communication network

5

The invention relates to an ISDN network with switching centers to which data-compatible terminals, e.g. in the form of computers with ISDN cards, are also connected, wherein the switching centers include a switching network and a coordination processor with user programs, and the network is configured to allow a exchange of data between the data-compatible terminals and the coordination processor as defined by the user programs.

15

Operator systems providing information and/or switching services are typical examples of data exchange between a data-compatible terminal and a digital switching center, where network-wide data connections are to be established between the terminals of operator-console systems and the digital controller of a digital exchange.

20

According to known proposals, a data connection is established over the ISDN D channel in order to transfer internal data, though network-wide transfer via the network is not possible between port-based user programs. However, the small data volume that can be transferred per time unit, which is theoretically 16 kbit/s for an ISDN D channel (though this transfer rate is only partially achieved), has an adverse effect in practice, since the D channel is also used for ISDN signaling, as a result of which it cannot be used for relatively large data volumes, such as occur for example in the case of software updates requiring several Mbytes.

25

30

35

WO 98/17079 (Siemens Aktiengesellschaft) describes a method for handling service connections in a digital network, which enables a subscriber with a digital

terminal to access the Internet via the fastest possible path. A suitable switching center contains what is known as a "POP" server, to which a line trunk group is assigned, and where the POP server is a
5 hardware platform.

However, the present application concerns a switching center that includes a coordination processor with user programs that relate to operator consoles, for example, where large data volumes may occur.

10 The object of the invention is to specify a means by which relatively large data volumes can be transferred over data connections between data-compatible terminals and the software of the coordination processor in a switching center, with
15 facilities for sending large data volumes automatically, e.g. at times of low network utilization.

Based on an ISDN network of the type described at the beginning, the invention achieves this
20 object by installing a hardware platform in at least one switching center, said hardware platform being assigned a unique call number throughout the network, and a direct bus connection being provided between this hardware platform and the coordination processor, the
25 platform implementing the data traffic with the terminals via B channels and the coordination processor being configured in conjunction with a user program to dial up terminals directly via a subscriber call number.

30 Using the invention, a data-compatible terminal can dial up the hardware platform directly, so that data from the user programs can be sent to the terminals via the direct bus connection. Since the data traffic now flows via B channels of the ISDN network,
35 it is possible to transfer considerably greater data

10-30-2000

199805815

- 2a -

DE 009903633

volumes, i.e. up to 64 kbit/s and, if necessary, the intelligent digital switching center can also establish a data connection with a data-compatible terminal.

5 For transferring relatively large data volumes, it is also expedient to configure the hardware platform to support data traffic with a terminal via both B channels.

10 For security reasons, it is also possible to assign the hardware platform a call number that cannot be dialed.

Patent claims

1. An ISDN network with switching centers (VST1, VST2),
to which data-compatible terminals (EG1, EG2), e.g. in
5 the form of computers with ISDN cards are also
connected, wherein the switching centers include a
switching network (KNE) and a coordination processor
(COP) with user programs (UPR1, UPR2 and UPR3), and
wherein the network is configured to allow an exchange
10 of data between the data-compatible terminals and the
coordination processor as defined by the user programs,
characterized in that a hardware platform (HWP) is
installed in at least one switching center (VST2) and
is assigned a unique call number throughout the
15 network, and a direct bus connection (BUV) is provided
between this hardware platform and the coordination
processor (COP), where the platform implements the data
traffic with the terminals (EG1, EG2) via B channels,
and the coordination processor (COP) is configured in
20 conjunction with a user program (UPR1, 2, ...) to dial up
terminals (EG1, EG2) directly via a subscriber call
number.

2. The ISDN network as claimed in claim 1 or 2,
25 characterized in that the hardware platform (HWP) is
configured to support data traffic with a terminal
(EG1, EG2) via both B channels.

3. The ISDN network as claimed in claim 1 or 2,
30 characterized in that the call number assigned to the
hardware platform (HWP) is a "non-dialable" call
number.

4. The ISDN network as claimed in one of claims 1 to 3,
35 characterized in that the hardware platform (HWP) is
directly connected to the ports of a line trunk group
(LTG).

VERSIONS WITH MARKINGS TO SHOW CHANGES MADE

In The Specification:

The Specification of the present application, including the Abstract, has been amended as follows:

SPECIFICATION

TITLE

5 ~~Method for handling service connections in a communication network~~
ISDN NETWORK WITH A HARDWARE PLATFORM IN SWITCHING
CENTERS

BACKGROUND OF THE INVENTION

Description

10 Field of the Invention

The present invention relates to an ISDN network with switching centers to which data-compatible terminals, e.g. in the form of computers with ISDN cards, are also connected, wherein the switching centers include a switching network and a coordination processor with user programs, and the network is configured to allow a
15 an exchange of data between the data-compatible terminals and the coordination processor as defined by the user programs.

Description of the Prior Art

Operator systems providing information and/or switching services are typical examples of data exchange between a data-compatible terminal and a digital switching
20 center, where network-wide data connections are to be established between the terminals of operator-console systems and the digital controller of a digital exchange.

According to known proposals, a data connection is established over the ISDN D channel in order to transfer internal data, though network-wide transfer via the network is not possible between port-based user programs. However, the small data
25 volume that can be transferred per time unit, which is theoretically 16 kbit/s for an ISDN D channel (though this transfer rate is only partially achieved), has an adverse effect in practice, since the D channel is also used for ISDN signaling, as As a result,

09856841-09901
JC18 Rec'd 707/TO 2 5 MAY 2001

of which it cannot be used for relatively large data volumes, such as, ~~occur~~ for example, in the case of software updates requiring several Mbytes.

WO 98/17079 (Siemens Aktiengesellschaft) describes a method for handling service connections in a digital network, which enables a subscriber with a digital terminal to access the Internet via the fastest possible path. A suitable switching center contains what is known as a "POP" server, to which a line trunk group is assigned, and where the POP server is a hardware platform.

However, the present application concerns a switching center that includes a coordination processor with user programs that relate to operator consoles, for example, where large data volumes may occur.

SUMMARY OF THE INVENTION

~~The object of~~ Accordingly, the present invention is to specify a means directed to a way by which relatively large data volumes can be transferred over data connections between data-compatible terminals and the software of the coordination processor in a switching center, with facilities for sending large data volumes automatically; e.g., at times of low network utilization.

Based on an ISDN network of the type described at the beginning, the present invention achieves this ~~object~~ by installing a hardware platform in at least one switching center, ~~said~~ the hardware platform being assigned a unique call number throughout the network, and a direct bus connection being provided between this hardware platform and the coordination processor, ~~the~~ The platform implementing implements the data traffic with the terminals via B channels and the coordination processor ~~being is~~ configured in conjunction with a user program to dial up terminals directly via a subscriber call number.

Using the present invention, a data-compatible terminal can dial up the hardware platform directly, so that data from the user programs can be sent to the terminals via the direct bus connection. Since the data traffic now flows via B channels of the ISDN network, it is possible to transfer considerably greater data volumes, i.e. up to 64 kbit/s and, if necessary, the intelligent digital switching center can also establish a data connection with a data-compatible terminal.

For transferring relatively large data volumes, it is also expedient to configure the hardware platform to support data traffic with a terminal via both B channels.

For security reasons, it is also possible to assign the hardware platform a call number that cannot be dialed.

5 Additional features and advantages of the present invention are described in, and will be apparent from, the following Detailed Description of the Preferred Embodiments and the Drawings.

~~The invention and other advantages are described in greater detail below in an exemplary embodiment, and with reference to the drawing, in which:~~

10 **DESCRIPTION OF THE DRAWINGS**

Figure 1 shows the schematic layout of a switching center with a connected terminal and a state-of-the-art operator console; and

Figure 2 schematically shows an ISDN network of the present invention with two switching centers, together with connected terminals or operator consoles.

15 **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

According to ~~figure~~ Figure 1, a local switching center LVS has a coordination processor COP, a switching network KNE, and an access unit ASE. A data-compatible terminal EGE may consist of a PC with an ISDN card ISC, for example, and this PC has access to user programs UPR. Using an ISDN basic access IBA, data can be

20 transferred with the switching center LVS over the ISDN D channel. As described in, for example "ISDN - Digitale Netze für Sprachen, Text, Daten, Video und Multimedia-Kommunikation" [ISDN - digital networks for voice, text, data, video and multimedia communication] by Peter Bocker, 4th edition, Springer Verlag 1997, ISBN 3-45-57431-X, each basic access gives a user two 64-kbit/s basic channels, known as B

25 channels, and one 16-kbit/s auxiliary channel, known as the D channel, in each direction. The data stream from a number of ISDN basic ~~accesses~~ accesses, up to approximately 500 in practice, is concentrated in the access units ASE onto a message channel with 64 kbit/s leading to the coordination processor COP, and the data are routed to the individual user programs UPR1, UPR2 and UPR3 from there. Such user

30 programs may be implemented to manage or support a switching operation, for

example, where an operator console OPP is provided, ~~e.g. such as~~ for manual switching. The switching center LVS shown in ~~figure~~ Figure 1 is a local switching center, and provides the only data connection available to the terminal EGE. No network-wide data connections are therefore possible, in addition to which the data transfer is restricted to 16 kbit/s per terminal. Furthermore, the combination of several ISDN basic ~~accesses~~ accesses on one internal message channel of the switching center LVS creates an undesirable bottleneck.

By contrast, as shown in ~~figure~~ Figure 2, the present invention proposes a hardware platform HWP in a switching center LVSR, in addition to the coordination processor COP with the user programs UPR1, UPR2 and UPR3, and a switching network KNE which hardware platform HWP is connected directly to the ports of the line trunk group LTG on one side, and via a direct bus connection BUV to the coordination processor (COP) and its user programs UPR1, UPR2 and UPR3 on the other side. It should be noted that, in principle, a switching center LVSR can be implemented as ~~a~~ what is known as an EWSD (Siemens digital electronic switching system), as described in, for example, "Telekommunikationstechnik" [Telecommunications systems] by Ottfried Georg, in Chapter 7.3 of "Das Vermittlungssystem EWSD" [the EWSD switching system], Springer Verlag 1996, ISBN 3-45-61381-1.

As is evident, the actual ISDN network NET also includes other switching centers, ~~e.g. such as~~ the switching center LVSR shown on the left of the diagram with a switching network KNE and other equipment not shown here, to which a further terminal EGER is, in turn, connected via an ISDN basic access IBA, and where this terminal likewise includes an ISDN card ISC and user programs UPR.

During operation, the ISDN card ISC of a terminal EGE, for example, initiates an outgoing call over the B channel to the hardware platform, where it is expedient to use a "non-dialable" number for this purpose, e.g., "0F10". "Non-dialable" ~~means that~~ refers to the number ~~cannot~~ not being able to be dialed using a conventional keypad, which only has numbers, and is expedient for security reasons. The remote switching center, namely the switching center LVSR on the left of the diagram in this case,

analyzes the dialed number and routes the call through the public exchange to the destination switching center LVSR where the digits in the call number are analyzed, and traffic for the internal hardware platform HWP is identified. The next step is to find a free port for access to the hardware platform HWP, ~~and~~ this is being performed
5 by the routing functions of the switching center LVSR.

As mentioned previously, the ports assigned to the hardware platform HWP are connected within the switching center to the line trunk group LTG for outgoing lines or subscribers. The hardware platform HWP now handles the data transfer protocol with the terminals, and the hardware platform HWP transfers data to the user programs
10 UPR1, UPR2 and UPR3 in the coordination processor COP. Furthermore, the hardware platform HWP accepts data from the user programs and sends them to the terminals EGER. In this context, the hardware platform HWP is directly connected to the central controller, namely the coordination processor COP, via the bus connection BUV, and uses interprocessor messages to communicate with the user programs. The
15 user programs UPR1, UPR2 and UPR3 in the coordination processor COP receive the data from the hardware platform HWP. If a user program wants to send data back to the terminal EGER, it uses an interprocessor message to transfer them to the hardware platform, which can dial up terminals directly via a subscriber call number. It is also expedient for the hardware platform HWP to be configured to support data traffic with
20 a terminal via both B channels, in order to allow higher data throughput.

Although the present invention has been described with reference to specific embodiments, those of skill in the art will recognize that changes may be made thereto without departing from the spirit and scope of the invention as set forth in the hereafter appended claims.

Abstract

ABSTRACT OF THE DISCLOSURE

~~ISDN network with a hardware platform in switching centers~~

5 An ISDN network with switching centers (~~VST1, VST2~~), to which data-compatible terminals (~~EG1, EG2~~), e.g. in the form of computers with ISDN cards, are also connected, wherein the switching centers include a switching network (~~KNE~~) and a coordination processor (~~COP~~) with user programs (~~UPR~~), and wherein the network is configured to allow an exchange of data between the data-compatible terminals and the coordination processor as defined by the user programs, ~~furthermore~~ and wherein,
10 a hardware platform (~~HWP~~) is installed in at least one switching center (~~VST2~~) and is assigned a unique call number throughout the network, and a direct bus connection (~~BUV~~) is provided between this hardware platform and the coordination processor (~~COP~~), where the platform implements the data traffic with the terminals (~~EG1, EG2~~) via B channels.

15

Fig. 2

2/PRTS

09/856841

JC18 Rec'd TCT/PTC 25 MAY 2001

GR 98 P 5815

- 1 -

Description

ISDN network with a hardware platform in switching centers

5

The invention relates to an ISDN network with switching centers to which data-compatible terminals, e.g. in the form of computers with ISDN cards, are also connected, wherein the switching centers include a switching network and a coordination processor with user programs, and the network is configured to allow an exchange of data between the data-compatible terminals and the coordination processor as defined by the user programs.

15

Operator systems providing information and/or switching services are typical examples of data exchange between a data-compatible terminal and a digital switching center, where network-wide data connections are to be established between the terminals of operator-console systems and the digital controller of a digital exchange.

20

According to known proposals, a data connection is established over the ISDN D channel in order to transfer internal data, though network-wide transfer via the network is not possible between port-based user programs. However, the small data volume that can be transferred per time unit, which is theoretically 16 kbit/s for an ISDN D channel (though this transfer rate is only partially achieved), has an adverse effect in practice, since the D channel is also used for ISDN signaling, as a result of which it cannot be used for relatively large data volumes, such as occur for example in the case of software updates requiring several Mbytes.

25

30

35

The object of the invention is to specify a means by which relatively large data volumes can be transferred over data connections between data-

09/856841-0000

- 2 -

software of the coordination processor in a switching center

Based on an ISDN network of the type described at the beginning, the invention achieves this
5 object by installing a hardware platform in at least one switching center, said hardware platform being assigned a unique call number throughout the network, and a direct bus connection being provided between this hardware platform and the coordination processor, the
10 platform implementing the data traffic with the terminals via B channels.

Using the invention, a data-compatible terminal can dial up the hardware platform directly, so that data from the user programs can be sent to the
15 terminals via the direct bus connection. Since the data traffic now flows via B channels of the ISDN network, it is possible to transfer considerably greater data volumes, i.e. up to 64 kbit/s.

In an advantageous development of the
20 invention, the coordination processor is configured in conjunction with a user program to dial up terminals directly via a subscriber call number. This means that the intelligent digital switching center can also establish a data connection with a data-compatible
25 terminal if necessary.

For transferring relatively large data volumes, it is also expedient to configure the hardware platform to support data traffic with a terminal via both B channels.

30 For security reasons, it is also possible to assign the hardware platform a call number that cannot be dialed.

- 3 -

The invention and other advantages are described in greater detail below in an exemplary embodiment, and with reference to the drawing, in which:

5 Figure 1 shows the schematic layout of a switching center with a connected terminal and a state-of-the-art operator console.

 Figure 2 schematically shows an ISDN network with two switching centers, together with connected
10 terminals or operator consoles.

 According to figure 1, a local switching center LVS has a coordination processor COP, a switching network KNE, and an access unit ASE. A data-compatible terminal EGE may consist of a PC with an
15 ISDN card ISC, for example, and this PC has access to user programs UPR. Using an ISDN basic access IBA, data can be transferred with the switching center LVS over the ISDN D channel. As described in, for example "ISDN -
 Digitale Netze für Sprachen, Text, Daten, Video und
20 Multimedia-Kommunikation" [ISDN - digital networks for voice, text, data, video and multimedia communication] by Peter Bocker, 4th edition, Springer Verlag 1997, ISBN 3-45-57431-X, each basic access gives a user two
 64-kbit/s basic channels, known as B channels, and one
25 16-kbit/s auxiliary channel, known as the D channel, in each direction. The data stream from a number of ISDN basic accesss, up to approximately 500 in practice, is concentrated in the access units ASE onto a message channel with 64 kbit/s leading to the coordination
30 processor COP, and the data are routed to the individual user programs UPR1, UPR2 and UPR3 from there. Such user programs may be implemented to manage or support a switching operation, for example, where an operator console OPP is provided, e.g. for manual
35 switching. The switching center LVS shown in figure 1 is a local switching center, and provides the only data connection available to the terminal EGE. No network-wide data connections are therefore

- 4 -

possible, in addition to which the data transfer is restricted to 16 kbit/s per terminal. Furthermore, the combination of several ISDN basic accesss on one internal message channel of the switching center LVS
5 creates an undesirable bottleneck.

By contrast, as shown in figure 2, the invention proposes a hardware platform HWP in a switching center LVSR, in addition to the coordination processor COP with the user programs UPR1, UPR2 and
10 UPR3, and a switching network KNE which hardware platform HWP is connected directly to the ports of the line trunk group LTG on one side, and via a direct bus connection BUV to the coordination processor (COP) and its user programs UPR1, UPR2 and UPR3 on the other
15 side. It should be noted that, in principle, a switching center LVSR can be implemented as a what is known as an EWSD (Siemens digital electronic switching system), as described in, for example, "Telekommunikationstechnik" [Telecommunications
20 systems] by Ottfried Georg, in Chapter 7.3 of "Das Vermittlungssystem EWSD" [the EWSD switching system], Springer Verlag 1996, ISBN 3-45-61381-1.

As is evident, the actual ISDN network NET also includes other switching centers, e.g. the
25 switching center LVSR shown on the left of the diagram with a switching network KNE and other equipment not shown here, to which a further terminal EGEr is in turn connected via an ISDN basic access IBA, and where this terminal likewise includes an ISDN card ISC and user
30 programs UPR.

During operation the ISDN card ISC of a terminal EGE, for example, initiates an outgoing call over the B channel to the hardware platform, where it is expedient to use a "non-dialable" number for this
35 purpose, e.g. "0F10". "Non-dialable" means that the number cannot be dialed using a conventional keypad, which only has numbers, and is expedient for security reasons. The remote switching center, namely the

GR 98 P 5815

- 4a -

switching center LVSR on the left of the diagram in
this case, analyzes the dialed number and routes the

0985815 P5815

- 5 -

5 to find a free port for access to the hardware platform
HWP, and this is performed by the routing functions of
the switching center LVSR.

10 switching center to the line trunk group LTG for
outgoing lines or subscribers. The hardware platform
HWP now handles the data transfer protocol with the
terminals, and the hardware platform HWP transfers data
to the user programs UPR1, UPR2 and UPR3 in the
15 coordination processor COP. Furthermore, the hardware
platform HWP accepts data from the user programs and
sends them to the terminals EGER. In this context, the
hardware platform HWP is directly connected to the
central controller, namely the coordination processor
20 COP, via the bus connection BUV, and uses
interprocessor messages to communicate with the user
programs. The user programs UPR1, UPR2 and UPR3 in the
coordination processor COP receive the data from the
hardware platform HWP. If a user program wants to send
25 data back to the terminal EGER, it uses an
interprocessor message to transfer them to the hardware
platform, which can dial up terminals directly via a
subscriber call number. It is also expedient for the
hardware platform HWP to be configured to support data
30 traffic with a terminal via both B channels, in order
to allow higher data throughput.

Patent claims

1. An ISDN network with switching centers (VST1, VST2), to which data-compatible terminals (EG1, EG2), e.g. in the form of computers with ISDN cards, are also connected, wherein the switching centers include a switching network (KNE) and a coordination processor (COP) with user programs (UPR), and wherein the network is configured to allow an exchange of data between the data-compatible terminals and the coordination processor as defined by the user programs, characterized in that a hardware platform (HWP) is installed in at least one switching center (VST2) and is assigned a unique call number throughout the network, and a direct bus connection (BUV) is provided between this hardware platform and the coordination processor (COP), where the platform implements the data traffic with the terminals (EG1, EG2) via B channels.

2. The ISDN network as claimed in claim 1, characterized in that the coordination processor (COP) is configured in conjunction with a user program (UPR1, 2, ...) to dial up terminals (EG1, EG2) directly via a subscriber call number.

3. The ISDN network as claimed in claim 1 or 2, characterized in that the hardware platform (HWP) is configured to support data traffic with a terminal (EG1, EG2) via both B channels.

4. The ISDN network as claimed in one of claims 1 to 3, characterized in that the call number assigned to the hardware platform (HWP) is a "non-dialable" call number.

5. The ISDN network as claimed in one of claims 1 to 4, characterized in that the hardware platform (HWP) is directly connected to the ports of a line trunk group (LTG).

Abstract


ISDN network with a hardware platform in switching centers

5

10 An ISDN network with switching centers (VST1, VST2), to which data-compatible terminals (EG1, EG2), e.g. in the form of computers with ISDN cards, are also connected, wherein the switching centers include a switching network (KNE) and a coordination processor (COP) with user programs (UPR), and wherein the network is configured to allow an exchange of data between the data-compatible terminals and the coordination processor as defined by the user programs, furthermore, 15 a hardware platform (HWP) is installed in at least one switching center (VST2) and is assigned a unique call number throughout the network, and a direct bus connection (BUV) is provided between this hardware platform and the coordination processor (COP), where 20 the platform implements the data traffic with the terminals (EG1, EG2) via B channels.

Fig. 2

1/2

**Fig. 1 (State of the art)**




Fig. 2

Declaration and Power of Attorney For Patent Application
Erklärung Für Patentanmeldungen Mit Vollmacht
German Language Declaration

Als nachstehend benannter Erfinder erkläre ich hiermit an Eides Statt:

As a below named inventor, I hereby declare that:

dass mein Wohnsitz, meine Postanschrift, und meine Staatsangehörigkeit den im Nachstehenden nach meinem Namen aufgeführten Angaben entsprechen,

My residence, post office address and citizenship are as stated below next to my name,

dass ich, nach bestem Wissen der ursprüngliche, erste und alleinige Erfinder (falls nachstehend nur ein Name angegeben ist) oder ein ursprünglicher, erster und Miterfinder (falls nachstehend mehrere Namen aufgeführt sind) des Gegenstandes bin, für den dieser Antrag gestellt wird und für den ein Patent beantragt wird für die Erfindung mit dem Titel:

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

ISDN-Netz mit einer Hardware-Plattform
in Vermittlungsstellen

ISDN-network with a hardware-platform
in switching centres

deren Beschreibung

the specification of which

(zutreffendes ankreuzen)

(check one)

☐ hier beigefügt ist.

☐ is attached hereto.

☒ am 15.11.1999 als

☒ was filed on 15.11.1999 as

PCT internationale Anmeldung

PCT international application

PCT Anmeldungsnummer PCT/DE99/03633

PCT Application No. PCT/DE99/03633

eingereicht wurde und am _____

and was amended on _____

abgeändert wurde (falls tatsächlich abgeändert).

(if applicable)

Ich bestätige hiermit, dass ich den Inhalt der obigen Patentanmeldung einschliesslich der Ansprüche durchgesehen und verstanden habe, die eventuell durch einen Zusatzantrag wie oben erwähnt abgeändert wurde.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above.

Ich erkenne meine Pflicht zur Offenbarung irgendwelcher Informationen, die für die Prüfung der vorliegenden Anmeldung in Einklang mit Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) von Wichtigkeit sind, an.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

Ich beanspruche hiermit ausländische Prioritätsvorteile gemäss Abschnitt 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 119 aller unten angegebenen Auslandsanmeldungen für ein Patent oder eine Erfindersurkunde, und habe auch alle Auslandsanmeldungen für ein Patent oder eine Erfindersurkunde nachstehend gekennzeichnet, die ein Anmeldedatum haben, das vor dem Anmeldedatum der Anmeldung liegt, für die Priorität beansprucht wird.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

1998P05815WOUS

German Language Declaration

Prior foreign applications
Priorität beansprucht

Priority Claimed

19854419.7

DE

25.11.1998

☒

☐

(Number)
(Nummer)

(Country)
(Land)

(Day Month Year Filed)
(Tag Monat Jahr eingereicht)

Yes
Ja

No
Nein

(Number)
(Nummer)

(Country)
(Land)

(Day Month Year Filed)
(Tag Monat Jahr eingereicht)

☐
Yes
Ja

☐
No
Nein

(Number)
(Nummer)

(Country)
(Land)

(Day Month Year Filed)
(Tag Monat Jahr eingereicht)

☐
Yes
Ja

☐
No
Nein

Ich beanspruche hiermit gemäss Absatz 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 120, den Vorzug aller unten aufgeführten Anmeldungen und falls der Gegenstand aus jedem Anspruch dieser Anmeldung nicht in einer früheren amerikanischen Patentanmeldung laut dem ersten Paragraphen des Absatzes 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 122 offenbart ist, erkenne ich gemäss Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) meine Pflicht zur Offenbarung von Informationen an, die zwischen dem Anmeldedatum der früheren Anmeldung und dem nationalen oder PCT internationalen Anmeldedatum dieser Anmeldung bekannt geworden sind.

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §122, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

PCT/DE99/03633

(Application Serial No.)
(Anmeldeseriennummer)

15.11.1999

(Filing Date D, M, Y)
(Anmeldedatum T, M, J)

(Status)
(patentiert, anhängig,
aufgegeben)

(Status)
(patented, pending,
abandoned)

(Application Serial No.)
(Anmeldeseriennummer)

(Filing Date D,M,Y)
(Anmeldedatum T, M, J)

(Status)
(patentiert, anhängig,
aufgeben)

(Status)
(patented, pending,
abandoned)

Ich erkläre hiermit, dass alle von mir in der vorliegenden Erklärung gemachten Angaben nach meinem besten Wissen und Gewissen der vollen Wahrheit entsprechen, und dass ich diese eidesstattliche Erklärung in Kenntnis dessen abgebe, dass wissentlich und vorsätzlich falsche Angaben gemäss Paragraph 1001, Absatz 18 der Zivilprozessordnung der Vereinigten Staaten von Amerika mit Geldstrafe belegt und/oder Gefängnis bestraft werden koennen, und dass derartig wissentlich und vorsätzlich falsche Angaben die Gültigkeit der vorliegenden Patentanmeldung oder eines darauf erteilten Patentes gefährden können.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

German Language Déclaration

VERTRETUNGSVOLLMACHT: Als benannter Erfinder beauftrage ich hiermit den nachstehend benannten Patentanwalt (oder die nachstehend benannten Patentanwälte) und/oder Patent-Agenten mit der Verfolgung der vorliegenden Patentanmeldung sowie mit der Abwicklung aller damit verbundenen Geschäfte vor dem Patent- und Warenzeichenamt: (Name und Registrationsnummer anführen)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

(SEE ATTACHED SHEET)

Customer No.

And I hereby appoint

Telefongespräche bitte richten an:
(Name und Telefonnummer)

Direct Telephone Calls to: (name and telephone number)

Ext. _____

Postanschrift:

Send Correspondence to:

Bell, Boyd & Lloyd LLC
70 West Madison Street, Suite 3300 60602-4207 Chicago, Illinois
Telephone: +1 312 372 1121 and Facsimile +1 312 372 2098

or

Customer No.

Voller Name des einzigen oder ursprünglichen Erfinders:		Full name of sole or first inventor:	
CHRISTIAN MAIERHOFER		CHRISTIAN MAIERHOFER	
Unterschrift des Erfinders	Datum	Inventor's signature	Date
	7.5.2001		
Wohnsitz		Residence	
A-3180 LILIENFELD, ÖSTERREICH		A-3180 LILIENFELD, AUSTRIA	
Staatsangehörigkeit		Citizenship	
AT		AT	
Postanschrift		Post Office Address	
JUNGHERRNTALSTR. 4		JUNGHERRNTALSTR. 4	
A-3180 LILIENFELD		A-3180 LILIENFELD	
Voller Name des zweiten Miterfinders (falls zutreffend):		Full name of second joint inventor, if any:	
Unterschrift des Erfinders		Second Inventor's signature	
Datum		Date	
Wohnsitz		Residence	
Staatsangehörigkeit		Citizenship	
Postanschrift		Post Office Address	

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).

17
Holby M. Abern (P47,372), Robert M. Barrett (30,142), Alan L. Barry (30,819), Thomas C. Basso (46,541), Jeffrey H. Canfield (38,404), Robert W. Connors (46,639), Amy J. Gast (41,773), James Jagoda (33,250), Patricia A. Kane (46,446), Michael S. Leonard (37,557), Edward A. Lehman (22,312), Adam H. Masia (35,602), Dante J. Picciano (33,543), Renato L. Smith (45,117), Maurice E. Teixeira (45,646), William E. Vaughan (39,056), Austin Victor (47,154), and all members of the firm of Bell, Boyd & Lloyd LLC.

William E. Vaughan
Bell, Boyd & Lloyd LLC
P.O. Box 1135
Chicago, Illinois 60690

William E. Vaughan
312.807.4292

312.807.4292